

"Easyflex" Level Mounts for Vibration/Shock/Noise Isolation

Here's All You Have To Do

- Move machine into place.
- Raise Machine
- Attach Mounts and lower machine.
Adjust leveling screws until machine is level.



"Easyflex" Mounts Take only a Few Minutes to Install.

Economy & Advantages

- "Easy Flex" Level-Mounts require no expense for floor preparation, bolts, anchor plates, masonry Drilling and re-cementing.
- Built-in levelling adjustment saves time, labour and money.
- Mounts are practically indestructible and match the life of mounted machine.
- No Foundation * Flexible Production Lines * Shock & Vibration Isolation * Reduced Maintenance & Less Noise
- Available in Oil Resistant Nitrile Rubber.

| Size | Load Capacity lbs | Standard Bolt Size | Length inch/mm |
|----------------|-------------------|--------------------|----------------|
| Type : SC - 12 | (Heavy Duty) | | |
| EFLM-090/SC-12 | 1980 - 2970 | 1/2"/M 12 | 4"/100mm |
| EFLM-110/SC-12 | 2970 - 4400 | 5/8"/M 16 | 5"/125mm |
| EFLM-128/SC-12 | 3960 - 5940 | 5/8"/M 16 | 5"/125mm |
| EFLM-156/SC-12 | 5940 - 8910 | 3/4"/M 20 | 6"/150mm |
| EFLM-180/SC-12 | 7920 - 11880 | 3/4"/M 20 | 6"/150mm |
| EFLM-210/SC-12 | 10780 - 16060 | 1"/M 24 | 8"/200mm |
| EFLM-240/SC-12 | 14080 - 21120 | 1"/M 24 | 8"/200mm |
| EFLM-300/SC-12 | 22000 - 33000 | As per requirement | |
| EFLM-400/SC-12 | 38720 - 58740 | As per requirement | |

Note : To be used with Load Factor