




Features

EFSRH Spring Hangers consist of freestanding, laterally stable steel springs in series with a molded elastomeric element assembled into a stamped and welded hanger bracket. The hanger brackets and the springs are powder coated. Spring vibration isolation hangers are designed to provide high efficiency isolation from structure-borne vibration and noise. Springs are color-coded and in compliance with ASHRAE guidelines, springs are designed with a horizontal stiffness of at least 100% of the vertical stiffness, to ensure stability. This is achieved through high spring diameter to operating height ratios - 0.85 to 1.0 (as against the minimum of 0.80 required by ASHRAE).. These Hangers are double deflection Hangers specially suitable for Seismic Applications.



F (Rod & Hardware by others)

Applications

EFSRH Hangers are used to isolate suspended sources of both noise and vibration. Suspended mechanical equipment such as false ceiling, air handling units, FCU's cabinet fans, piping and ductwork in close proximity to rotating mechanical equipment are typical applications of model EFSRH hangers.

Compliance - Springs designed according to BS 1726 (Part 1) and recommendations made by SAE (US) and ASHRAE

ISOLATOR MODEL	COLOR CODE	RATED LOAD (lbs)	DEFLECTION (inch)	M (inch)	L (inch)	W (inch)	H (inch)	F (inch)	TOP HOLE (inch)
EFSRH 20/15	WHITE	33	0.79	2.09	2.44	2.05	3.94	0.39	0.47
EFSRH 20/30	YELLOW	66	0.79	2.09	2.44	2.05	3.94	0.39	0.47
EFSRH 20/50	PURPLE	110	0.79	2.09	2.44	2.05	3.94	0.39	0.47

ISOLATOR MODEL	COLOR CODE	RATED LOAD (lbs)	DEFLECTION (inch)	M (inch)	L (inch)	W (inch)	H (inch)	F (inch)	TOP HOLE (inch)
EFSRH 25/10	PURPLE	22	0.98	2.09	2.44	2.05	4.92	0.47	0.55
EFSRH 25/15	YELLOW	33	0.98	2.09	2.44	2.05	4.92	0.47	0.55
EFSRH 25/20	GREY	44	0.98	2.09	2.44	2.05	4.92	0.47	0.55
EFSRH 25/40	LIGHT BLUE	88	0.98	2.09	2.44	2.05	4.92	0.47	0.55
EFSRH 25/60	GREEN	132	0.98	2.09	2.44	2.05	4.92	0.47	0.55
EFSRH 25/100	GREEN	220	0.98	3.27	3.54	2.60	6.50	0.55	0.59
EFSRH 25/160	ORANGE	352	0.98	3.27	3.54	2.60	6.50	0.55	0.59
EFSRH 25/200	RED	440	0.98	3.27	3.54	2.60	6.50	0.55	0.59
EFSRH 25/250	PURPLE	551	0.98	3.27	3.54	2.60	6.50	0.55	0.59
EFSRH 25/300	GREY	661	0.98	3.74	4.02	3.74	7.87	0.63	0.71
EFSRH 25/400	ORANGE	881	0.98	3.74	4.02	3.74	7.87	0.63	0.71
EFSRH 25/500	BROWN	1102	0.98	3.74	4.02	3.74	7.87	0.63	0.71
EFSRH 25/600	BLACK	1322	0.98	3.74	4.02	3.74	7.87	0.63	0.71
EFSRH 25/800	RED	1763	0.98	3.74	4.02	3.74	7.87	0.63	0.71
EFSRH 25/1050	WHITE	2314	0.98	3.74	4.02	3.74	7.87	0.63	0.71
EFSRH 25/1250	GREEN	2755	0.98	3.74	4.02	3.74	7.87	0.63	0.71

- Due to policy of continual improvement, the specifications are subject to change without prior notice.
- Measurements are subject to 5% tolerance.
- To achieve good sound suppression do not over load fitting.