

Easyflex

TM

Wrap-on Flexible Duct Style : EFWODC

Vv VibraSystems




FLEXIBILITY	: $\pm 0.375''$ OR MORE
TEMPERATURE	: UPTO 100°C
PRESSURE RANGE	: -118.11" WC. TO +118.11" WC.
STANDARD WIDTH	: 6" / 8"
STANDARD LENGTH	: UPTO 5 Meter Rolls

Available in 3 basic types :


- Full Width Fabric.
 - With GI / Aluminum Metal edges covered with fabric.
 - With GI / Aluminum Metal edges partly covered with fabric.
- Easyflex WRAP-ON Flexible Duct Connector will met every type of installation requirement in hospitals, offices, large buildings, factories, institutions etc.
 - Maximum design freedom - does not need to be excessively large than ducting.
 - Connectors will effectively isolate Vibration, Noise & Rattles resulting from operation of Fans & blowers.
 - Connectors will protect duct work and ancillary equipment from the effect of Vibration, Movements & Misalignment.
 - Connectors can be used on both cool and warm side of air conditioning systems - highly suitable for duct carrying heavily moisture laden air.

Durable construction - Neoprene impregnated and leak proofed fabric is fire retardant, resists grease, gasoline vapours, acids, moisture, mildew, etc.


- Tear resistant.
- Excellent flexing properties.
- Low resistance to deflection.
- Combination of metal & fabric give added strength & flexibility.
- Fire Retardent Neoprene Rubber




VIBRATION ISOLATION



AXIAL EXPANSION



AXIAL CONTRACTION



LATERAL DEFLECTION

- Higher Thickness/Length/Polymers available please contact our engineering department.