



The 6 sizes of the standard EFSRF range are a practical and versatile support solution for pipe work and cable trays. They can also be used for smaller outdoor condensing units or air source heat pump installations. The feet have a 1.61" x 0.83" 'bonded' in channel, which is recessed into the top face allowing you to use standard strut fixings to secure your services to the feet.

Our EFSFR range are made from Recycled SBR rubber, making them eco friendly. They also have the added advantage of vibration and noise absorption which makes them the perfect product for roof or ground level installation.



| Model | A (inch) | B (inch) | C (inch) | D (inch) | MAX Load Capacity (lbs/pc) |
|-----------|-------------|-------------|-------------|-------------|----------------------------------|
| EFSFR250 | 9.84 | 6.42 | 3.86 | 8.27 | 330 |
| EFSFR400 | 15.75 | 6.42 | 3.86 | 14.17 | 352 |
| EFSFR500 | 19.69 | 5.12 | 2.56 | 18.11 | 418 |
| EFSFR600 | 23.62 | 6.42 | 3.86 | 22.08 | 551 |
| EFSFR1000 | 39.37 | 6.42 | 3.86 | 37.80 | 881 |



| Model | A (mm) | B (mm) | C (mm) | D (mm) | MAX Load Capacity (kg/pc) |
|----------|-----------|-----------|-----------|-----------|---------------------------------|
| EFSFR110 | 4.33 | 4.33 | 2.68 | 2.28 | 1110 |

Material Specification

SBR-Recycled Rubber. Bound using a ratio of high quality moisture curing Polyurethane Pre-Polymer. BS7188:1989+A2;2009 and BS EN1176-7:2008

Metal Profile

Aluminium strut 1.61" x 0.83" profile compatible with strut fixings.

Working Conditions

Suitable for internal or external applications in temperatures between -40°C to +80°C. BSEN60068-2-14